



## ***e/m-Flex™* EMFLX-M10004-GPI** **2dB Ground Plane Independent Antenna** **132-174 MHz**

- High Performance, Broadband Impedance Match
- Optimized VSWR for Maximum “No Ground Plane” Efficiency
- Black Chrome Finish with Flexible Polymer Alloy Spring
- O-ring Seals for Waterproof Construction
- Durable Xenoy™ Base with TPV Molded Dust Seal and Grip Ring

### Electrical Specifications

Frequency Band	132-174 MHz (Tunable Range)
Operational Bandwidth	15-20 MHz (frequency dependent)
VSWR	<1.2:1 at center frequency
	<2:1 across operational bandwidth
Impedance	50Ω
Gain	2 dBi
Power Rating	150 W
Polarization	Linear, Vertical
E-Plane	70 Degrees, Nominal
H-Plane	Omnidirectional

### Mechanical Specifications

Overall Length (max)	50 in. (1.27 m)
Whip Material, Finish	17-7 SS, Black Chrome
Base Material	Xenoy™ w/TPV over mold grip ring
Mounting Application	¾ inch thru-hole NMO Mount
Spring Material	Black Molded Polymer Alloy
NMO Cable Assembly & Connector	Sold separately
Operating Temperature	-40° to 85° C
Corrosion	Salt Fog
Humidity	95%

Specifications subject to change without notification.