

## EM-M11001-195 NMO 3/4" Hole Mount Assembly



- Low-Profile
- Ease of installation: Designed for a one-man installation from above
- All brass components with silver plated contact
- Heavy-duty mounting claw for reliable contact and ground connections
- Premium double shielded foam PE, low loss cable – Standard

### Electrical Specifications

Frequency Band	30 – 1000 MHz
VSWR <sup>1</sup>	1.5:1 typical
Impedance	50Ω
Cable Insertion Loss	2 dB, max
Power Rating <sup>2</sup>	100 W @1000 MHz

### Mechanical Specifications

Mounting Height	0.375 in. (9.5 mm)
Mounting Hole	0.75 in. (19.05 mm)
Outside Mounting Diameter	1.13 in. (28.7 mm)
Mounting Application / Type	Thru-hole
Cable <sup>3</sup>	Low Loss Foam Polyethylene
Cable Length	17 ft. (5.1 m)
Connector Type	Sold separately
Mounting Material	Brass
Mounting Material Finish	Clear Iridite
Operating Temperature Range	-40° to 85° C
Mounting Surface Weather Seal	O-Ring
Corrosion	Salt Fog
Humidity	95%

1. Antenna / Frequency Dependent    2. VSWR, Temperature and Altitude Dependent    3. Other cable types available upon request